

A



**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**



Applicant: Hisayuki FURUSE

Title: ELECTRIC ROTATING MACHINE AND  
MANUFACTURING METHOD THEREOF

Appl. No.: Unassigned

Filing Date: October 3, 2000

Examiner: Unassigned

Art Unit: Unassigned

**UTILITY PATENT APPLICATION**  
**TRANSMITTAL**

Commissioner for Patents  
Box PATENT APPLICATION  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. § 1.53(b) is the nonprovisional utility patent application of:

Hisayuki FURUSE

Enclosed are:

- [ X ] Specification, Claim(s), and Abstract (12 pages).
- [ X ] Formal drawings (10 sheets, Figures 1-10).
- [ X ] Unexecuted Declaration and Power of Attorney (3 pages).
- [ X ] Information Disclosure Statement (2 pages).
- [ X ] Form PTO-1449 with copy of 1 listed reference.

09/678311 10/03/00

The filing fee is calculated below:


	Claims as Filed	Included in Basic Fee	Extra Claims	Rate	Fee Totals
Basic Fee				\$710.00	\$710.00
Total Claims:	9	- 20	= 0	x \$18.00	= \$0.00
Independents:	2	- 3	= 0	x \$80.00	= \$0.00
Surcharge Under 37 CFR 1.16(e)				\$130.00	\$130.00
If any Multiple Dependent Claim(s) present:				+ \$270.00	= \$0.00
				SUBTOTAL:	= \$840.00
[ ] Small Entity Fees Apply (subtract ½ of above):					= \$0.00
				TOTAL FILING FEE:	= \$840.00

- [ ] A check in the amount of \$0.00 to cover the filing fee is enclosed.
- [ X ] The required filing fees are not enclosed but will be submitted in response to the Notice to File Missing Parts of Application.
- [ ] The Commissioner is hereby authorized to charge any additional fees which may be required regarding this application under 37 C.F.R. §§ 1.16-1.17, or credit any overpayment, to Deposit Account No. 19-0741. Should no proper payment be enclosed herewith, as by a check being in the wrong amount, unsigned, post-dated, otherwise improper or informal or even entirely missing, the Commissioner is authorized to charge the unpaid amount to Deposit Account No. 19-0741.

Please direct all correspondence to the undersigned attorney or agent at the address indicated below.

Respectfully submitted,

By



Richard L. Schwaab  
Attorney for Applicant  
Registration No. 25,479

Date October 3, 2000

FOLEY & LARDNER  
Washington Harbour  
3000 K Street, N.W., Suite 500  
Washington, D.C. 20007-5109  
Telephone: (202) 672-5414  
Facsimile: (202) 672-5399

- 1 -

## **ELECTRIC ROTATING MACHINE AND MANUFACTURING METHOD THEREOF**

### **FIELD OF THE INVENTION**

The present invention relates to an electric rotating machine, such as a motor and generator, and in particular to an electric rotating machine wherein one stator and two rotors are arranged coaxially.

### **BACKGROUND OF THE INVENTION**

A rotator core and stator core of an electric rotating machine are formed of layers of thin plates such as silicon-steel plate. Generally, thin plates are joined by welding. However, since a convex projection arises in the welding position, the gap between the cores cannot be made small. That is, if the gap is made small, the core facing the convex projection will interfere with the convex projection.

Hence, the opposite side of a magnetic pole-face is welded so that there is no weld part with a surface (magnetic pole-face) facing another core.

### **SUMMARY OF THE INVENTION**

However, in the electric rotating machine in which one stator and two rotors are arranged coaxially as disclosed by JP-A-H9-275673 published by the Japanese Patent Office in 1997, both the inner and external surfaces of a core in the middle are magnetic pole-faces, so the opposite side of the magnetic pole-face cannot be

09678344 100300

welded as mentioned above.

If one of the surfaces is welded, the gap with the core facing the welded surface cannot be made small.

It is therefore an object of this invention to eliminate the above-mentioned convex projection, and make the gap between cores small.

In order to achieve above object, this invention provides an electric rotating machine, comprising a middle core comprising plural plates (2A, 23A) stacked in an axial direction, an outer core disposed outside the middle core, and which rotates relative to the middle core, and an inner core disposed inside the middle core, and which rotates relative to the middle core. The plural plates are joined to a first fixing member by a connecting member.

According to an aspect of the invention, this invention provides a method of manufacturing an electric rotating machine, the machine having a middle core comprising plural plates stacked in an axial direction, an outer core disposed outside the middle core which rotates relative to the middle core, and an inner core disposed inside the middle core which rotates relative to the middle core, the method comprising joining the plural plates to a first fixing member by a connecting member, and finishing the inner and outer circumferential surfaces of the plural plates in the state where the plural plates are joined only to the first fixing member.

The details as well as other features and advantages of this invention are set forth in the remainder of the specification and are shown in the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

000001 FEB 26 1960

Fig. 1 shows a schematic cross-sectional view of an electric rotating machine according to this invention.

Fig. 2 shows a thin plate forming an external rotor core of the electric rotating machine.

Fig. 3 shows a schematic cross-sectional view of the electric rotating machine during assembly.

Fig. 4 shows the left flange of the electric rotating machine.

Fig. 5 shows the detailed cross-sectional view of the electric rotating machine.

Fig. 6 is similar to Fig. 1, but showing a second embodiment of this invention.

Fig. 7 shows a thin plate forming the stator core of the electric rotating machine of the second embodiment.

Fig. 8 shows the fixed plate of the electric rotating machine of the second embodiment.

Fig. 9 shows a schematic cross-sectional view of the electric rotating machine of the second embodiment during assembly.

Fig. 10 shows a detailed cross-sectional view of the electric rotating machine of the second embodiment.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Fig. 1 of the drawings, an electric rotating machine of this invention is equipped with an inner rotor core 1 (inner core), an outer rotor core 2 (middle core), and a stator core 3 (outer core) in a housing 7. The outer rotor core 2 is arranged outside the inner rotor core 1, and the stator core 3 is arranged

outside the outer rotor core 2. The inner rotor core 1 and the outer rotor core 2 rotate relative to each other, and the outer rotor core 2 and stator core 3 also rotate relative to each other.

The inner rotor core 1, outer rotor core 2 and stator core 3 are respectively formed in stacks of plural thin silicon steel plates in the axial direction. The inner rotor core 1 is supported by a shaft 4. The outer rotor core 2 is fixed to a right flange 5 and a left flange 6. The stator 3 is fixed to the housing 7.

The electric rotating machine shown in Fig. 1 is manufactured as follows.

In the inner rotor core 1 and stator core 3, only the surfaces facing the outer rotor core 2 are magnetic pole-faces, so the stacked thin plates can be joined by welding the opposite sides to the magnetic pole-faces. After welding, the parts corresponding to the magnetic pole-faces of the joined thin plates are surface-finished.

However, both the inner circumferential surface and outer circumferential surface of the outer rotor core 2 are magnetic pole-faces, so the thin plates cannot be joined by welding. Therefore, holes 2B are provided in the thin plates 2A forming the outer rotor core 2, as shown in Fig. 2, and the plates are joined by passing bolts 9 through these holes 2B.

Specifically, first, plural thin plates 2A are stacked, and fixed to the right flange 5 by bolts 9 together with a plate 8. Next, as shown in Fig. 3, the right flange 5 to which the thin plates 2A and plate 8 are pre-attached is fitted on a chuck 100 of a grinding machine, and then the inner circumferential surface and outer circumferential surface of the outer rotor core 2 are ground with a grindstone 101 by rotating them. As the upper side of the figure is open, the inner circumferential surface of the outer rotor core 2 can easily be surface-finished. Here, grinding is

used as the surface-finishing method, but other surface-finishing method may be used if the inner circumferential surface and outer circumferential surface of the outer rotor core 2 can be surface-finished by it.

After surface-finishing is complete, the inner rotor which is pre-assembled beforehand is inserted, and attached via a bearing.

Plural holes 11 through which the heads of the bolts 9 pass and plural holes 12 which have a seat for a fixing bolt 10 are alternately formed on the same circumference in the left flange as shown in Fig. 4. The outer rotor core 2 is fixed to the left flange 6 by the bolts 10.

Therefore, the outer core 2 is fixed to the right flange 5 by the bolts 9 (for example, three or more bolts on the same circumference) and is not fixed to the left flange 6 in the state shown in Fig. 3, but after the inner rotor core 1 is inserted in the outer rotor core 2, it is fixed to both the left flange 6 and right flange 5 by the bolts 10 (for example, three or more bolts on the same circumference).

The outer rotor core 2, right flange 5, left flange 6, plate 8 and bolts 9 are formed in one piece to form the outer rotor.

Holes, not shown, in which permanent magnets are disposed, are provided in the inner rotor core 1 and the outer rotor core 2. Parts, not shown, in which coils are installed, are provided in the stator core 3. These permanent magnets and coils are pre-attached to the rotor cores 1 and 2 or the stator core 3 prior to assembly.

Therefore, both the inner circumferential surface and outer circumferential surface are magnetic pole-faces, but according to this invention, the inner circumferential surface and outer circumferential surface can be finished in the state where only one side is attached to the right flange 5, so machining of the inner

circumferential surface is easy. Hence, the magnetic pole-faces can be finished precisely and the gap between cores can be made small. Moreover, since welding is not used, the magnetic pole-faces are protected.

Fig. 5 shows a detailed cross section of the electric rotating machine shown in Fig. 1. In Fig. 1, the construction is simplified so that it is easy to understand. The shape of structural components is different between Fig. 1 and Fig. 5, but components referred to by the same symbols are the same components.

The thin plates forming the inner core 1 and stator 3 are joined by welding, but holes may be opened in the thin plates forming these components as in the case of the outer rotor core 2 and they may be joined by bolts.

Fig. 6 shows a second embodiment of this invention.

The electric rotating machine of the second embodiment, as in the case of the electric rotating machine shown in Fig. 1, is equipped with an inner rotor core 21 (inner core), outer rotor core 22 (outer core) and stator core 23 (middle core) which rotate relative to each other in the housing. In this embodiment, the stator core 22 is disposed outside the inner rotor core 21, and the outer rotor core 22 is disposed outside the stator core 23.

The inner rotor core 21, outer rotor core 22 and stator core 23 are respectively formed in stacks of plural thin silicon steel plates. The inner rotor core 21 is supported by a shaft 24, and the outer rotor core 22 is supported by a shaft 25. The stator core 23 is fixed to a flange 26 by bolts 28 together with a plate 27.

Fig. 7 shows a thin-plate 23A which forms the stator core 23. The thin-plate 23A comprises plural I-shaped split cores 23B on the same circumference. A space 23C through which a bolt 28 passes is formed between adjacent split cores.

Fig. 8 shows the plate 27. Holes 27A which have a seat for the bolt 28 are



The electric rotating machine shown in Fig. 6 is manufactured as follows.

In the stator core 23, both the inner circumferential surface and outer circumferential surface are magnetic pole-faces, so the thin plates cannot be fixed by welding. The spaces 23C are thus provided in each thin plate 23A and the thin plates 23A are then fixed by passing the bolts 28 through the spaces 23C.

After surface finishing, the inner rotor assembled beforehand is inserted, and attached via a bearing. Also, the outer rotor assembled beforehand is attached to the outside of the stator via a bearing.

Holes, not shown, are provided for installing permanent magnets in the inner rotor core 21 and the outer rotor core 22, and parts, not shown, are provided for installing coils in the stator core 23. The permanent magnets and coils are respectively pre-attached to the rotor cores 21 and 22 or the stator core 23 prior to assembly.

Therefore, both the inner and outer circumferential surfaces are magnetic pole-faces, but the inner and outer surfaces are surface-finished when the stator core 23 is fixed only to the flange 26, so machining of the inner surface can be performed easily. The magnetic pole-faces can be finished precisely and the gap between cores can also be made small. Moreover, as welding is not used, the magnetic pole-faces are protected.

Fig. 10 shows a detailed cross section of the electric rotating machine shown in Fig. 6. In the schematic view of Fig. 6, shapes are drawn simplified for ease of understanding. The shapes of structural components are different between Fig. 6 and Fig. 10, but components referred to by the same number are identical components.

Herein, the thin plates forming the inner rotor core 21 and outer rotor core 22 are joined by welding, but holes may be opened in the thin plates forming them as in the case of the stator core 23, and they may then be joined by bolts.

This invention may be applied also to constructions other than those shown in Fig. 1 and Fig. 6. For example, this invention may be applied in a similar way to the inner rotor core of an electric rotating machine where the inner rotor core is disposed inside the outer rotor core and the stator core is disposed inside the inner rotor core by forming the inner rotor core in the same manner as shown in Fig. 1 or Fig 3.

The entire contents of Japanese Patent Application P11-282352 (filed October 4, 1999) are incorporated herein by reference.

Although the invention has been described above by reference to a certain embodiment of the invention, the invention is not limited to the embodiment described above. Modifications and variations of the embodiments described

Figure 1 consists of 12 sub-graphs labeled (a) through (l), each showing the growth of *E. coli* O157:H7 in ground beef under different treatment conditions. The y-axis for all graphs is  $\log_{10}$  CFU/g, ranging from 0 to 10. The x-axis is time in hours, ranging from 0 to 24. The graphs show various growth curves, with some treatments showing significant inhibition of growth compared to the control.

- (a) Control: Shows a typical growth curve, starting at  $\log_{10}$  CFU/g = 0 and reaching approximately 8.5 at 24 hours.
- (b) Salt: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (c) Acetic acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (d) Lactic acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (e) Citric acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (f) Malic acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (g) Succinic acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (h) Fumaric acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (i) Tartaric acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (j) Malic acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (k) Citric acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.
- (l) Lactic acid: Shows a growth curve similar to the control, reaching approximately 8.5 at 24 hours.

1. An electric rotating machine, comprising:

an outer core disposed outside the middle core, and which rotates relative to

an inner core disposed inside the middle core, and which rotates relative to the

wherein the plural plates are joined to a first fixing member by a connecting

2. An electric rotating machine as defined in Claim 1, wherein the connecting member is a bolt, and a hole through which the bolt passes is formed in the plural plates.

3. An electric rotating machine as defined in Claim 1, wherein the plates are ring-shaped thin plates.

4. An electric rotating machine as defined in Claim 1, wherein the middle core and inner core are rotor cores, and the outer core is a stator core.

5. An electric rotating machine as defined in Claim 1, wherein the middle core is a stator core, and the outer core and inner core are rotor cores.

6. An electric rotating machine as defined in Claim 5, wherein the stator core is

7. A **method** of manufacturing an electric rotating machine, the machine having a middle **core** comprising plural plates stacked in an axial direction, an outer core disposed **outside** the middle core which rotates relative to the middle core, and an inner core **disposed** inside the middle core which rotates relative to the middle core, and the **method** comprising:

8. A method of manufacturing an electric rotating machine as defined in Claim 7, further comprising joining the opposite side of the plural plates to the first fixing member, to a second fixing member after finishing.

9. A method of manufacturing an electric rotating machine as defined in Claim 7, wherein the connecting member is a bolt, a hole through which the bolt passes is formed in the plural plates, and the plural plates are joined to the first fixing member by passing the bolt through the hole.

An electric rotating machine is equipped with a middle core, an outer core disposed outside the middle core which rotates relative to the middle core, and an inner core disposed inside the middle core which rotates relative to the middle core. The middle core comprises plural plates disposed in an axial direction. The plural plates are connected in the axial direction by a connecting member, and joined to a first fixing member. The inner and outer circumferential surfaces are finished in the state where the plates are joined only to the first fixing member, and the opposite side to the first fixing member is joined to a second fixing member after finishing.





FIG. 1



**FIG. 2**



[illegible]

[illegible]








FIG. 6



**FIG. 7**





**FIG. 9**





**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I HEREBY DECLARE:

THAT my residence, post office address, and citizenship are as stated below next to my name;

THAT I believe I am the original, first, and sole inventor (if only one inventor is named below) or an original, first, and joint inventor (if plural inventors are named below or in an attached Declaration) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ELECTRIC ROTATING MACHINE AND MANUFACTURING METHOD THEREOF

(Attorney Docket No. 040356/0332)

the specification of which (check one)

       is attached hereto.

  X   was filed on October 3, 2000 as United States Application Number  
or PCT International Application Number \_\_\_\_\_  
and was amended on \_\_\_\_\_ (if applicable).

THAT I do not know and do not believe that the same invention was ever known or used by others in the United States of America, or was patented or described in any printed publication in any country, before I (we) invented it;

THAT I do not know and do not believe that the same invention was patented or described in any printed publication in any country, or in public use or on sale in the United States of America, for more than one year prior to the filing date of this United States application;

THAT I do not know and do not believe that the same invention was first patented or made the subject of an inventor's certificate that issued in any country foreign to the United States of America before the filing date of this United States application if the foreign application was filed by me (us), or by my (our) legal representatives or assigns, more than twelve months (six months for design patents) prior to the filing date of this United States application;

THAT I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment specifically referred to above;

THAT I believe that the above-identified specification contains a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the invention, and sets forth the best mode contemplated by me of carrying out the invention; and

THAT I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I HEREBY CLAIM foreign priority benefits under Title 35, United States Code §119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number	Country	Foreign Filing Date	Priority Claimed?	Certified Copy Attached?
11-282352	Japan	October 4, 1999	Yes	

I HEREBY CLAIM the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

U.S. Provisional Application Number	Filing Date

I HEREBY CLAIM the benefit under Title 35, United States Code, §120 of any United States application(s), or § 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application Number	PCT Parent Application Number	Parent Filing Date	Parent Patent Number

I HEREBY APPOINT the following registered attorneys and agents of the law firm of FOLEY & LARDNER to have full power to prosecute this application and any continuations, divisions, reissues, and reexaminations thereof, to receive the patent, and to transact all business in the United States Patent and Trademark Office connected therewith:

STEPHEN A. BENT	Reg. No. 29,768
DAVID A. BLUMENTHAL	Reg. No. 26,257
BETH A. BURROUS	Reg. No. 35,087
ALAN I. CANTOR	Reg. No. 28,163
WILLIAM T. ELLIS	Reg. No. 26,874
JOHN J. FELDHAUS	Reg. No. 28,822
PATRICIA D. GRANADOS	Reg. No. 33,683

JOHN P. ISACSON	Reg. No. 33,715
MICHAEL D. KAMINSKI	Reg. No. 32,904
LYLE K. KIMMS	Reg. No. 34,079
KENNETH E. KROSIN	Reg. No. 25,735
JOHNNY A. KUMAR	Reg. No. 34,649
GLENN LAW	Reg. No. 34,371
PETER G. MACK	Reg. No. 26,001
BRIAN J. MC NAMARA	Reg. No. 32,789
SYBIL MELOY	Reg. No. 22,749
RICHARD C. PEET	Reg. No. 35,792
GEORGE E. QUILLIN	Reg. No. 32,792
COLIN G. SANDERCOCK	Reg. No. 31,298
BERNHARD D. SAXE	Reg. No. 28,665
CHARLES F. SCHILL	Reg. No. 27,590
RICHARD L. SCHWAAB	Reg. No. 25,479
ARTHUR SCHWARTZ	Reg. No. 22,115
HAROLD C. WEGNER	Reg. No. 25,258

and I request that all correspondence be directed to:

Richard L. Schwaab  
 FOLEY & LARDNER  
 Washington Harbour  
 3000 K Street, N.W., Suite 500  
 Washington, D.C. 20007-5109

Telephone: (202) 672-5414  
 Facsimile: (202) 672-5399

I UNDERSTAND AND AGREE THAT the foregoing attorneys and agents appointed by me to prosecute this application do not personally represent me or my legal interests, but instead represent the interests of the legal owner(s) of the invention described in this application.

I FURTHER DECLARE THAT all statements made herein of my own knowledge are true, and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Name of first inventor	Hisayuki FURUSE
Residence	Yokosuka city, JAPAN
Citizenship	JAPAN
Post Office Address	25-13, Hirasaku 1-chome, Yokosuka city, Kanagawa, JAPAN
Inventor's signature	
Date	